

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1105B

SIMOTICS GP - 100 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_R/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S6 60%) - 155(F) to 130(B)																	
230	Δ	50	3.30	-/-	11.80	1425	20.0	81.5	82.6	81.5	0.85	0.78	0.65	5.4	2.4	2.6	IE1
400	Y	50	3.30	-/-	6.90	1425	20.0	81.5	82.6	81.5	0.85	0.78	0.65	5.4	2.4	2.6	IE1
460	Y	60	3.80	-/-	6.50	1725	19.1	85.0	85.8	84.8	0.86	0.80	0.68	6.0	2.2	2.3	IE1
IM B5 / IM 3001		FS 100 L		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 9.5 s 16.5 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz/60Hz	60 / 72 dB(A) ^{2) 3)}	62 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0078 kg m ²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S6 60%
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad, min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	22 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:
 I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_R/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1LE1002-1AB52-2FA4-Z Y99	rev. 2	creation date 2023-10-09 11:29		
© Siemens AG 2023					

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1105B

SIMOTICS GP - 100 L - IM B5 - 4p

Special design

Y99 special motor design S6 60%


Notes:

I_L/I_N = locked rotor current / current nominal
 M_L/M_N = locked rotor torque / torque nominal

1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load

3) Value is valid only for DOL operation with motor design 1C411

M_b/M_N = break down torque / nominal torque

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
SIEMENS	document type datasheet	document status released			
	title 1LE1002-1AB52-2FA4-Z Y99	document number			
© Siemens AG 2023	rev. 2	creation date 2023-10-09 11:29	language en	Page 2/2	