

INTERPUMP LongLife 2SC

THE202K



APPLICATIONS :



APPROVALS :

MED, RINA, BV, LLOYD'S, ABS, NKK, KR, DNV, CCS

APPLICABLE SPECIFICATIONS

exceed EN 857 2SC - ISO 11237

No-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Tested up to 1.000.000 cycles up to 1". Easy to install. SMOOTH COVER up to 1".

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Coverage: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluids: Mineral and biological oils, glicol-water based, water, lubricants.

working temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension dash size	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm			bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE202K-04	1/4"	6.4	04	13.3	430	6235	1720	24940	50	1.969	0.283	0.19	001C-04
THE202K-05	5/16"	8	05	14.8	400	5800	1600	23200	60	2.362	0.324	0.218	001C-05
THE202K-06	3/8"	9.5	06	17.1	350	5075	1400	20300	70	2.756	0.418	0.281	001C-06
THE202K-08	1/2"	12.7	08	20.4	310	4495	1240	17980	80	3.15	0.521	0.35	001C-08
THE202K-10	5/8"	16	10	23.5	280	4060	1120	16240	100	3.937	0.626	0.421	001C-10
THE202K-12	3/4"	19	12	27.6	240	3480	960	13920	120	4.724	0.764	0.513	001C-12
THE202K-16	1"	25.4	16	35.8	210	3045	840	12180	160	6.299	1.171	0.787	001C-16
THE202K-20	1.1/4"	31.8	20	43.1	160	2320	640	9280	250	9.843	1.53	1.028	001C-20
THE202K-24	1.1/2"	38.1	24	50.6	150	2175	600	8700	260	10.236	2.12	1.425	001C-24
THE202K-32	2"	50.8	32	63.5	100	1450	400	5800	360	14.173	2.795	1.878	001C-32
THE202K-40	2.1/2"	63.5	40	75.6	80	1160	320	4640	600	23.622	3.224	2.167	001C-40
THE202K-48	3"	76.2	48	88	65	943	260	3770	760	29.921	3.471	2.333	001C-48

Available with MSHA and Mega cover. In case of order use code THE02K and THEV02K.

Marking: Available only "mylar"