

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV112B

SIMOTICS GP - 112 M - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

## Electrical data

## Safe Area

U [V]	$\Delta / Y$	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta$ <sup>3)</sup>			$\cos\phi$ <sup>3)</sup>			$I_A/I_N$ $I_f/I_N$	$M_A/M_N$ $T_f/T_N$	$M_R/M_N$ $T_B/T_N$	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
<b>DOL duty (S6 60%) - 155(F) to 130(B)</b>																	
400	$\Delta$	50	4.30	-/-	9.20	1435	26.5	83.1	84.3	84.0	0.83	0.77	0.65	6.1	2.5	2.9	IE1
690	Y	50	4.30	-/-	5.30	1435	26.5	83.1	84.3	84.0	0.83	0.77	0.65	6.1	2.5	2.9	IE1
460	$\Delta$	60	4.90	-/-	8.90	1735	25.0	85.0	86.1	85.1	0.83	0.78	0.66	6.8	2.5	3.2	IE1
IM B35 / IM 2001		FS 112 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 7.3 s   14.5 s								

## Mechanical data

Sound level (SPL / SWL) at 50Hz/60Hz	58 / 70 dB(A) <sup>2) 3)</sup>	62 / 74 dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.0100 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6206 2Z C3	6206 2Z C3	Duty type	S6 60%
<b>bearing lifetime</b>			Direction of rotation	bidirectional
$L_{10mh}$ $F_{Rad, min}$ for coupling operation 50 60Hz <sup>1)</sup>	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	27 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

## Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

**Notes:**  
 $I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_R/M_N$  = break down torque / nominal torque  
 1) L10mh according to DIN ISO 281 10/2010  
 2) at rated power / at full load  
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
	document type datasheet	document status released			
	title 1LE1002-1BB23-4JA4-Z Y99	document number			
© Siemens AG 2023	rev. 2	creation date 2023-10-09 11:36	language en		

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1112B

SIMOTICS GP - 112 M - IM B35 - 4p

## Special design


Y99 special motor design S6 60%

### Notes:

$I_L/I_N$  = locked rotor current / current nominal  
 $M_L/M_N$  = locked rotor torque / torque nominal  
 $M_b/M_N$  = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
 2) at rated power / at full load

3) Value is valid only for DOL operation with motor design 1C411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>SIEMENS</b>	document type datasheet	document status released			
	title <b>1LE1002-1BB23-4JA4-Z</b> Y99	document number			
© Siemens AG 2023	rev. 2	creation date 2023-10-09 11:36	language en	Page 2/2	