

# INTERPUMP LongLife 1SC

## APPLICATIONS:



## THE201K



## APPROVALS:

MED, RINA, BV, LLOYD'S, NKK, KR, DNV

## APPLICABLE SPECIFICATIONS

exceed EN 857 1SC- ISO 11237 1SC

No-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. SMOOTH COVER up to 1".

**Inner tube:** Synthetic rubber, extruded whole without joints, of uniform thickness.

**Reinforcement:** 1 high tensile steel wire braids.

**Coverage:** Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

**Recommended fluids:** Mineral and biological oils, glycol-water based, water, lubricants.

**working temperature:** from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension dash size	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm			bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE201K-04	1/4"	6.4	04	12.3	250	3625	1120	16240	50	1.969	0.182	0.122	001C-04
THE201K-05	5/16"	8	05	13.5	250	3625	1000	14500	55	2.165	0.21	0.141	001C-05
THE201K-06	3/8"	9.5	06	15.7	250	3625	1000	14500	60	2.362	0.248	0.167	001C-06
THE201K-08	1/2"	12.7	08	18.9	200	2900	800	11600	70	2.756	0.391	0.263	001C-08
THE201K-10	5/8"	16	10	22.4	150	2175	600	8700	90	3.543	0.41	0.276	001C-10
THE201K-12	3/4"	19	12	26	150	2175	600	8700	100	3.937	0.534	0.359	001C-12
THE201K-16	1"	25.4	16	33.7	110	1595	440	6380	180	7.087	0.742	0.499	001C-16
THE201K-20	1.1/4"	31.8	20	41.1	100	1450	400	5800	210	8.268	1.11	0.746	001C-20
THE201K-24	1.1/2"	38.1	24	48.6	90	1305	360	5220	300	11.811	1.39	0.934	001C-24
THE201K-32	2"	50.8	32	61.5	75	1088	300	4350	400	15.748	1.94	1.304	001C-32
THE201K-40	2.1/2"	63.5	40	73.5	50	725	200	2900	700	29.134	2.22	1.492	001C-40
THE201K-48	3"	76.2	48	86	40	580	160	2320	860	33.858	2.315	1.556	001C-48

Available with MSHA and Mega cover. In case of order use code THEV01K and THEV01K.

**Marking:** Available only "mylar"